FLOOR PLAN LEGEND

ENUATION INSULATION. REFER TO E WALL PARTITION SCHEDULE R RATED WALL R RATED WALL Approved for T HR RATED WALL

**PLAN ELEVATION** 

COMPLIANCE

LOCATIONS

FOR LOCATIONS

PORTABLE FIRE EXTINGUISHER

LINE INDICATES ORIENTATION OF KEYHOLE FOR FOR ANSI

SEMI-RECESSED FIRE EXTINGUISHER CABINET. INSTALL FIRE EXTINGUISHER SO THAT THE INTEGRITY OF RATED WALL IS MAINTAINED. CONTINUE TYPE X GYP BOARD ASSEMBLY

ENCROACH MORE THAN 4" INTO THE PATH OF EGRESS.

HEARING IMPAIRED UNIT, SEE MEP INFORMATION FOR ADDITIONAL REQUIREMENTS. SEE CODE FLOOR PLANS FOR

TYPE A FULLY ACCESSIBLE UNIT. SEE CODE FLOOR PLANS

REQUIRED 30"X48" WHEELCHAIR CLEARANCE. 48" SHALL BE

2'-10" MAXIMUM HEIGHT TO THE TOP OF THE KITCHEN OR BATHROOM SINK RIM. TYP. AT PUBLIC AREAS & TYPE A UNITS

AT ALL 1, 2 AND 3-BEDROOM PENTHOUSE UNITS U.N.O.

IN LIEU OF VTAC UNIT)

TYPICAL ACCESS PANEL LOCATION FOR

BE PAINTED TO MATCH ADJACENT WALL.

MECHANICAL UNIT. ACCESS PANEL TO

VTAC FLOOR PLAN DIAGRAM (VTAC UNIT TO BE INSTALLED AT TYPICAL) RESIDENTIAL LEVELS. AT PENTHOUSE

LEVEL ONLY, LOCATE CLOSET AND DOOR

CENTERED AT SINKS AND KITCHEN RANGE

Dwg. Coord.: Author Tech. Coord.: Checker LEVEL 4

14145 A140 FLOOR PLAN 02.05.2015 CD PERMIT / GMP SET

Phone: (614) 461-4664

CHANGE DESCRIPTION